

PRODUCT DESCRIPTION

ALTA BENTE KWARENTA SAE 20W-40 is a 4-stroke motorcycle engine oil specially formulated to provide excellent performance on 4-stroke motorcycles that are equipped with wet clutch system, operating under high stress and high temperature conditions. Superior engine protection against deposits and wear to prolong engine life. Reliable lubricating properties during start-stop riding cycles, ideal for Philippine traffic situation.

ALTA BENTE KWARENTA SAE 20W-40 is an all season engine oil, ready for the most demanding driving condition in the Philippines.

APPLICATION

- A reliable choice for use on all 4-stroke motorcycles - air and liquid cooled engines.
- For wet or dry clutch 4-stroke motorcycles.
- For 4-stroke motorcycle with catalytic converters.
- Suitable for use on underbones, mopeds, scooters, street bikes, ATV, utility vehicles and tricycles requiring API SG and JASO MA oils.

SPECIFICATIONS & PERFORMANCES

Standards : API SG, JASO MA

HEALTHY AND SAFETY

This product is not expected to cause any adverse health effects when used for intended purpose and in accordance to the recommendations from the product's Material Safety Data Sheet (MSDS). Do not dispose into drain or onto grounds, conserve and protect the environment. MSDS is available upon request.

CUSTOMER BENEFITS

✓ Reinforced with **360° PROtech**, KINETIC's core technology that ensure Performance, Reliability and Outstanding Protection to meet the daily needs of Philippine vehicles.



✓ Superior detergency and dispersancy for a cleaner engine, helping to prolong engine life.

✓ Reduces engine noise, excellent rust protection, and effectively dissipates heat to keep engine cool, protecting the engine, gearbox, and clutch.

✓ Ensures good friction control for easy gear shifts, acceleration and speed.

Always refer to the vehicle's maintenance manual before use. Do not store the product at temperatures over 60°C. Keep away from direct sunlight. Oil and filters must be replaced in accordance to vehicle's requirements.

TYPICAL CHARACTERISTICS

Properties	Unit	Test Method	Values
SAE Grade	-	SAE J300	20W-40
Density at 15°C	Kg/L	ASTM D445	0.881
Color	-	ASTM D1500	L3.0
Viscosity at 100°C	mm ² /s	ASTM D445	14.1
Viscosity at 40°C	mm ² /s	ASTM D445	118.5
Viscosity Index	-	ASTM D2270	120
TBN	mgKOH/g	ASTM D2896	6.3