

## PRODUCT DESCRIPTION

**PRIMERA KINSE KWARENTA SAE 15W-40** is a premium heavy-duty diesel engine oil specially formulated to provide excellent soot handling properties for On-highway and Off-highway heavy-duty vehicles, requiring API CH-4 oil. Its perfectly balanced detergent and dispersant additive technology provide exceptional engine durability of vehicles operating in severe conditions, helping to prolong engine life.

**PRIMERA KINSE KWARENTA 15W-40** is an all season engine oil, ready for the most demanding driving condition in the Philippines.

## APPLICATION

- Reliable partner of on-highway and off-highway heavy-duty diesel vehicles.
- A right choice for use on buses, trucks, off-highway vehicles, construction machineries, farm machineries, boats, generators and mixed fleet heavy-duty diesel engines requiring API CH-4 oil.
- Suitable for gasoline engines requiring API SL oils.

## SPECIFICATIONS & PERFORMANCES

Standards : API CH-4/SL

## HEALTHY AND SAFETY

This product is not expected to cause any adverse health effects when used for intended purpose and in accordance to the recommendations from the product's Material Safety Data Sheet (MSDS). Do not dispose into drain or onto grounds, conserve and protect the environment. MSDS is available upon request.

## CUSTOMER BENEFITS

✓ Reinforced with **360° PROtech**, KINETIC's core technology that ensure Performance, Reliability and Outstanding Protection to meet the daily needs of Philippine vehicles.



✓ Effectively controls oil thickening phenomenon to prevent the formation of harmful deposits, sludge, gums and varnish.

✓ Excellent detergent and dispersant properties to minimize soot formation, keeping engines clean and at tip-top condition.

✓ Effective protection against wear and corrosion.

*Always refer to the vehicle's maintenance manual before use. Do not store the product at temperatures over 60°C. Keep away from direct sunlight. Oil and filters must be replaced in accordance to vehicle's requirements.*

## TYPICAL CHARACTERISTICS

Properties	Unit	Test Method	Values
SAE Grade	-	SAE J300	15W-40
Density at 15°C	Kg/L	ASTM D445	0.885
Color	-	ASTM D1500	L3.0
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	14.7
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	123.9
Viscosity Index	-	ASTM D2270	123
TBN	mgKOH/g	ASTM D2896	11.4