

## PRODUCT DESCRIPTION

REKTA BENTE KWARENTA SAE 20W-40 is a 4-stroke motorcycle engine oil specially formulated to provide a durable protection on 4-stroke Philippine tricycles that are equipped with wet clutch system, operating under heavy load and high temperature conditions. Outstanding lubricating properties to reduce friction and wear, prolonging the engine life.

REKTA BENTE KWARENTA SAE 20W-40 is an all season engine oil, ready for the most demanding driving condition in the Philippines.

## APPLICATION

- A right choice for use on Philippine tricycles operating under severe conditions.
- Suitable for use on other 4-stroke motorcycles such as motorbikes, underbones, mopeds, and scooters requiring API SF and JASO MA2 oils.

## SPECIFICATIONS & PERFORMANCES

Standards : API SF, JASO MA

## HEALTHY AND SAFETY

This product is not expected to cause any adverse health effects when used for intended purpose and in accordance to the recommendations from the product's Material Safety Data Sheet (MSDS). Do not dispose into drain or onto grounds, conserve and protect the environment. MSDS is available upon request.

## CUSTOMER BENEFITS

✓ Reinforced with **360° PROtech**, KINETIC's core technology that ensure Performance, Reliability and Outstanding Protection to meet the daily needs of Philippine vehicles.



✓ Effective anti-wear, detergent and dispersant components to guarantee high level of cleanliness and protection on 3 major parts of motorcycle – engine, gearbox and clutch.

✓ Ensures good friction control to prevent clutch slippage, maintaining a smooth clutch operation.

✓ Good protection against corrosion.

*Always refer to the vehicle's maintenance manual before use. Do not store the product at temperatures over 60°C. Keep away from direct sunlight. Oil and filters must be replaced in accordance to vehicle's requirements.*

## TYPICAL CHARACTERISTICS

Properties	Unit	Test Method	Values
SAE Grade	-	SAE J300	20W-40
Density at 15°C	Kg/L	ASTM D445	0.881
Color	-	ASTM D1500	L3.0
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	14.6
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	117.1
Viscosity Index	-	ASTM D2270	123
TBN	mgKOH/g	ASTM D2896	5.4